

Wide-body Dump Truck SWK90

◆Gross weight: 90t ◆Rated load: 60t ◆Transmission input torque: 2200N·m ◆Body capacity: 33m³

Strong power !

More carrying capacity !

More durability !



◆Strong power

With a special engine, it can achieve higher torque output at low rotation speed and stronger power in heavy-duty uphill, and can save fuel in comparison with the like products.

◆High-quality component configuration

Wabco brake valve, all-aluminum fuel tank and air storage tank can ensure the safety of brake control and prolong the service life.

◆More carrying capacity

The carrying capacity is increased 10% by the heavy load frame and suspension system specially designed for the mine the performance is more reliable.

◆Wide field of vision

The cab newly designed it is equipped with hyperboloid integral arc front windscreen enables a wider field of vision and improved driving safety.

◆High power auxiliary braking

The engine in-cylinder braking technology is adopted to effectively ensure the driving safety, and assure the service braking system of a longer service life and less maintenance.





Outline dimension (L×W×H)		mm	9000×3450×3750
Max. gross weight		t	90
Rated load weight		t	60
Net weight		t	30
Drive type			6×4
Wheel base		mm	3775+1550
Wheel tread (front/rear)		mm	2680 / 2500
Min. ground clearance		mm	300
Approach angle / angle of departure		°	29 / 48
Max. speed		km/h	40
Max. gradeability		%	≥35
Body capacity		m ³	33
Max. lifting angle of box bucket		°	48
Engine	Model		YC6K460-GT30
	Power	kW/rpm	338/1900
Transmission	Model		7DS220
	Input torque	N·m	2200
Axle	Load (front axle/middle axle/rear axle)	t	25 / 35 / 35
Tire	Model		14.00-25
Body	Dimension of inner chamber	mm	5800×3200×1800
	Thickness of plate (bottom plate/side plate/rear door)	mm	16 / 12 / 14
	Materials	mm	High-strength wear-resistant plate

★ The above parameters may change due to product update



PT. SICOMA INDO PERKASA

Ruko THE ICON H/5 Jl. Raya Cisauk-Lapan BSD Tangerang 15343

Tlp: 021-22232607 Email: info@sicoma.co.id

@sicomaindonesia

SUNWARD